



Product Service

# CERTIFICATE

No. Z2 111130 0001 Rev. 00

**Holder of Certificate:** **MYLIGHT SYSTEMS S.A.S.**

1609 Avenue Henri Schneider  
ZAC des Gaulnes  
69330 Jonage  
FRANCE

**Certification Mark:**



**Product:**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-crystalline Silicon Photovoltaic Module**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 701262100301-00

**Valid until:** 2026-01-17

**Date,** 2021-01-20

( Zhulin Zhang )

# CERTIFICATE

No. Z2 111130 0001 Rev. 00

## Model(s):

1500 V DC Maximum System voltage, Fire Safety Class C Modules:

MYL-xxx-6MA-HV(xxx=330-400 in step of 5W)  
MYL -xxx-6MB-HV(xxx=275-330 in step of 5W )  
MYL -xxx-E01A-HV(xxx=365-420 in step of 5W)  
MYL -xxx-E01B-HV(xxx=305-350 in step of 5W)  
MYL -xxx-BMA-HV(xxx=330-445 in step of 5W)  
MYL -xxx-BMB-HV(xxx=275-370 in step of 5W)  
MYL -xxx-BMC-HV(xxx=305-380 in step of 5W)  
MYL -xxx-BMZ-HV(xxx=425-450 in step of 5W)  
MYL -xxx-E6A-HV(xxx=410-435 in step of 5W)  
MYL -xxx-E6B-HV(xxx=350-370 in step of 5W)

1000 V DC Maximum System voltage, Fire Safety Class C Modules:

MYL -xxx-6MA (xxx=330-400 in step of 5W)  
MYL -xxx-6MB (xxx=275-330 in step of 5W)  
MYL -xxx-E01A(xxx=365-420 in step of 5W)  
MYL -xxx-E01B(xxx=305-350 in step of 5W)  
MYL -xxx-BMA(xxx=330-445 in step of 5W)  
MYL -xxx-BMB(xxx=275-370 in step of 5W)  
MYL -xxx-BMC(xxx=305-380 in step of 5W)  
MYL -xxx-BMZ(xxx=425-450 in step of 5W)  
MYL -xxx-E6A (xxx=410-435 in step of 5W)  
MYL -xxx-E6B (xxx=350-370 in step of 5W)

1500 V DC Maximum System voltage, Fire Safety Class A Modules:

MYL -xxx-6MA-BG (xxx=350-395 in step of 5W)  
MYL -xxx-6MB-BG (xxx=295-325 in step of 5W)  
MYL -xxx-6MA-DG (xxx=350-395 in step of 5W)  
MYL -xxx-6MB-DG (xxx=295-325 in step of 5W)  
MYL-xxx-BMA-BG (xxx=350-445 in step of 5W)  
MYL-xxx-BMA-BG (xxx=525-540 in step of 5W)  
MYL-xxx-BMB-BG (xxx=290-370 in step of 5W)  
MYL-xxx-BMB-BG (xxx=440-450 in step of 5W)  
MYL-xxx-BMC-BG (xxx=320-375 in step of 5W)  
MYL-xxx-BMC-BG (xxx=485-495 in step of 5W)  
MYL-xxx-BMD-BG (xxx=395-405 in step of 5W)  
MYL-xxx-BMA-DG (xxx=350-425 in step of 5W)  
MYL-xxx-BMB-DG (xxx=290-350 in step of 5W)  
MYL-xxx-BMC-DG (xxx=320-350 in step of 5W)  
MYL-xxx-BMZ-BG (xxx=425-450 in step of 5W)  
xxx is standing for rated output power at STC.

## Parameters:

Safety Class:	Class II
Max. System Voltage:	1000V DC or 1500V DC
Test Laboratory:	Changzhou HuaYang Inspection and Testing Technology Co., Ltd No.8 Lanxiang Road Wujin Economic Development Zone Changzhou, Jiangsu, China.
Construction:	Framed or Frameless, with Junction box, cable and connector.
Fire Safety Class:	Class C or Class A according to UL790



# CERTIFICATE

No. Z2 111130 0001 Rev. 00

**Tested according to:**  
IEC 61215-1(ed.1)  
IEC 61215-1-1(ed.1)  
IEC 61215-2(ed.1)  
IEC 61730-1(ed.2)  
IEC 61730-2(ed.2)

**Production Facility(ies):** 076729, 098633, 104590, 108867, 098455